

Grounding conductor for lightning discharge. Kit includes: conductor (tape or round wire according EN 50164-2), stainless steel conductor holders and miscellaneous system accessories and fixing hardware.

The item is supply with and without insulator.

Custom products can be supplied to customers specific requirement.

Product specifications of insulator:

- material fiber-reinforced plastic
- electric insulation  $\leq 2\text{kV}$
- operating temperature  $-40 +130^{\circ}\text{C}$
- terminal M8 thread

How to order

Specify structure length.

Article	Type	Section	Material	Supply configuration	Installation example
GRWK 0015	wire	50 mm <sup>2</sup>	Cu		
GRWK 0017	wire	70 mm <sup>2</sup>	Cu		
GRWK 0026	tape	60 (30x2 mm)	Cu/Sn		
GRWK 0031	tape	105 (30x3.5 mm)	Fe/Zn		
GRWK 0115	wire	50 mm <sup>2</sup>	Cu		
GRWK 0117	wire	70 mm <sup>2</sup>	Cu		
GRWK 0126	tape	60 (30x2 mm)	Cu/Sn		
GRWK 0131	tape	105 (30x3.5 mm)	Fe/Zn		
GRWK 1015	wire	50 mm <sup>2</sup>	Cu		
GRWK 1017	wire	70 mm <sup>2</sup>	Cu		
GRWK 1026	tape	60 (30x2 mm)	Cu/Sn		
GRWK 1031	tape	105 (30x3.5 mm)	Fe/Zn		
GRWK 1115	wire	50 mm <sup>2</sup>	Cu		
GRWK 1117	wire	70 mm <sup>2</sup>	Cu		
GRWK 1126	tape	60 (30x2 mm)	Cu/Sn		
GRWK 1131	tape	105 (30x3.5 mm)	Fe/Zn		

Legend

Cu Copper  
Cu/Sn Copper with tin coating

Fe/Zn Zinc-coating steel  
(70 μm - mean value 500 gr/m<sup>2</sup>)